

## FEATURES

- Horizontal or vertical Rod core chokes
- Printed circuit board mounting
- High saturation current : suitable for high pulsed currents

## APPLICATIONS

- Differential mode filtering in high current outputs of Switch Mode Power Supplies
- General power inductor use in all kind of electronic equipment

RC / H					
IND	IND. Tol.	IDC max.	Isat max.	R max.	Référence
$\mu\text{H}$		A	A	m $\Omega$	
1	M	5	20	6	79300
1,8	M	7	22	6	79301
2,2	L	2	5	20	79302
2,4	M	12	27	4	79303
3,3	L	2	11	32	79304
3,3	L	4,7	17	12	79305
4,7	K	1,1	3,2	60	79306
4,7	L	3,2	13	24	79307
4,7	L	6,5	19	8	79308
4,7	M	18	38	3	79309
5,6	L	13	21	4,5	79310
10	K	2	9,5	60	79311
10	K	3,3	12	30	79312
10	K	8,5	16	10	79313
10	L	10,5	26	9	79314
15	K	6,2	13	18	79315
15	K	8	22	15	79316
30	K	4,3	14	45	79317

### Inductance tolerance

K : +/- 10%  
L : +/- 15%  
M : +/- 20%

### Operating temperature range

-25 / +85°C