

# Power Socket - System Rails 63A, 400 VAC

for Cable and Construction Site / Temporary Supply Distribution Cabinets

## Components for 185mm systems

Power socket - system rails are designed for temporary installations up to 63A in distribution cabinets / cable and construction site.

### Features Benefits

- Installation on to 185 mm bus bar system  
M12 bus bar termination, tightening torque  $M = 35 \pm 3 \text{ Nm}$
- For temporary installations up to 63 A with protected connection
- One device containing back-up fuse, MCB; RCD and power sockets
- Design with power sockets for 400 V and 230 V AC
- System compatibility (width of device 100 mm)  
Power socket - system rails can be replaced by NH-fuse rails or NH-vertical fuse switch disconnectors (identical width of device)

### Applications

- Temporary supply distribution cabinets
- Cable and construction site

### Technical data overview

Volt (VAC)	400 VAC
Amper (A)	63 A
Mounting	bus bar system 185 mm




### Standards

DIN EN 60439-1  
VDE 0660 part 500  
IEC 60439-1:199 + A :2004

# Power Socket - System Rails 63A, 400 VAC

for Cable and Construction Site / Temporary Supply Distribution Cabinets



## Product range



1.002.760



1.002.762

### Power socket - system rails 32 A - 63 A 230 V - 400 V

Catalog number	Reference number	Design	Weight kg <sup>1)</sup>	Package
1.002.760	W1024600	D02-fuse base triple pole (pre-fuse device) RCCB 40/4/0,03 A; 2 x MCB C 16/triple pole 2 x CEE-socket 400 V, 16 A, 5-polig	5.50	1 piece
1.002.761	X1024601	D02-fuse base triple pole (pre-fuse device) RCCB 40/4/0,03 A; 2 x MCB C 32/triple pole 2 x CEE-socket 400 V, 32 A, 5-polig	4.60	1 piece
1.002.762	Y1024602	D02-fuse base triple pole (pre-fuse device) RCCB 40/4/0,03 A; 4 x MCB C 16/single pole 4 x protective contact-socket 230 V, 16 A	4.60	1 piece
1.002.763	Z1024603	D02-fuse base triple pole (pre-fuse device) RCCB 40/4/0,03 A; 2 x MCB C 16/single pole 2 x protective contact-socket 230 V, 16 A 1 x CEE-socket 400 V, 1 x MCB C 16/triple pole	4.60	1 piece
1.003.145	A1024604	D02-fuse base triple pole (pre-fuse device) RCCB 63/0,03 A 1 x CEE-socket 400 V, 63 A, 5-pole	4.50	1 piece

1) weight in kg per piece or set including package