

Data sheet CP 341 (341-1CH01)

Technical data

| | |
|--|--|
| Order no. | 341-1CH01 |
| Type | CP 341 |
| General information | |
| Note | - |
| Features | RS422/485 Isolated Function compatibility to Siemens CP 341 Parameterization via the Siemens parameterization package Data transfer rate up to 76,8 Kbit/s Power supply via backplane bus |
| SPEED-Bus | - |
| Current consumption/power loss | |
| Current consumption from backplane bus | 160 mA |
| Power loss | 0.8 W |
| Status information, alarms, diagnostics | |
| Status display | yes |
| Interrupts | no |
| Process alarm | no |
| Diagnostic interrupt | yes, parameterizable |
| Diagnostic functions | no |
| Diagnostics information read-out | possible |
| Supply voltage display | yes |
| Group error display | red SF LED |
| Channel error display | none |
| Functionality Sub-D interfaces | |
| Type | X2 |
| Type of interface | RS422/485 |
| Connector | Sub-D, 9-pin, female |
| Electrically isolated | yes |
| MPI | - |
| MP2I (MPI/RS232) | - |
| Point-to-point interface | yes |
| 5V DC Power supply | max. 90mA, isolated |
| 24V DC Power supply | - |
| Functionality Sub-D interfaces | |
| Type | - |
| Type of interface | - |
| Connector | - |
| Electrically isolated | - |
| MPI | - |
| MP2I (MPI/RS232) | - |
| Point-to-point interface | - |
| 5V DC Power supply | - |
| 24V DC Power supply | - |

Point-to-point communication

| | |
|--------------------------|----------------------|
| PtP communication | yes |
| Interface isolated | yes |
| RS232 interface | - |
| RS422 interface | yes |
| RS485 interface | yes |
| Connector | Sub-D, 9-pin, female |
| Transmission speed, min. | 150 bit/s |
| Transmission speed, max. | 76.8 kbit/s |
| Cable length, max. | 1200 m |

Point-to-point protocol

| | |
|------------------------|-----|
| ASCII protocol | yes |
| STX/ETX protocol | yes |
| 3964(R) protocol | yes |
| RK512 protocol | - |
| USS master protocol | - |
| Modbus master protocol | yes |
| Modbus slave protocol | yes |
| Special protocols | - |

Datasizes

| | |
|------------------|------------|
| Input bytes | 16 |
| Output bytes | 16 |
| Parameter bytes | (16 + 106) |
| Diagnostic bytes | 4 |

Housing

| | |
|----------|-----------------|
| Material | PPE |
| Mounting | Rail System 300 |

Mechanical data

| | |
|------------------------------|-------------------------|
| Dimensions (WxHxD) | 40 mm x 125 mm x 120 mm |
| Net weight | 170 g |
| Weight including accessories | - |
| Gross weight | - |

Environmental conditions

| | |
|-----------------------|-----------------|
| Operating temperature | 0 °C to 60 °C |
| Storage temperature | -25 °C to 70 °C |

Certifications

| | |
|------------------|-----|
| UL certification | yes |
| KC certification | yes |