MULTIVERT® 160A/60mm

PRODUCT RANGE

Size 00, 690VAC, Triple Pole Switching

MULTIVERT[®] 160 A size 00 60 mm bus bar system 1 x triple pole switching



1.000.909

Catalog number	ltem number	Cable termination components	Design	Package	Weight
1.000.909	E1002183	3 M8 terminal screws/3 clamp straps 4-70 mm ²	bottom terminal with cover shroud MZ00KH	1 piece	1.45 kg
1.002.489	Z1023154	3 frame clamps Cu 2,5-70 mm ²	bottom terminal with cover shroud MZ00KH	1 piece	1.3 kg
1.003.140	A1023155	3 M8 terminal screws/3 clamp straps 4-70 mm ²	bottom terminal MULTIVERT® 1.000.909 with cabling of instrument leads	1 piece	1.5 kg
1.003.307	C1023157	3 M8 terminal screws/3 clamp straps 4-70 mm ²	top terminal with cover shroud MZ00KH	1 piece	1.5 kg
1.003.308	D1023158	3 M8 terminal screws/3 clamp straps 4-70 mm ²	top terminal MULTIVERT [®] 1.003.307 with cabling of instrument leads	1 piece	1.5 kg
1.003.309	E1023159	3 frame clamps Cu 2,5-70 mm ²	top terminal with cover shroud MZ00KH	1 piece	1.3 kg

ACCESSORIES



MZ00KA

MZ00KH

Cover/shrouds for cable termination

Catalog number	ltem number	Design	Package	Weight
MZ00KH	F1023298	cover shroud length 106 mm for MULTIVERT®/BSL 160 A	1 piece	20 g
MZ00KA	L1023464	extended cover shroud for cover shroud MZ00KH	1 piece	40 g
1.000.915	H1023300	cover shroud for MULTIVERT®/BSL 160 A with V-terminal	1 piece	50 g



MZAW

Covers/level & system adjustment covers

Catalog number	ltem number	Design	Package	Weight
MZ00AAD	X214081	2 piece adjustment, with integrated area for labeling to adapt to $MULTIVERT^{\circ}$ for 185 mm bus bar system	1 set	0.1 kg
MZAW	D218687	support angle for support of cover plate 1 set = 4 pieces	1 set	27 g



MULTIVERT® 160A/60mm

1.002.939

1.000.852

Size 00, 690VAC, Triple Pole Switching

Indication facilities

Catalog number	Item number	Design	Package	Weight
1.002.939	Y1023452	electronic fuse monitoring ESÜ size 00 for MULTIVERT® 160 A with cabling of instrument leads (rated voltage 525VAC)	1 piece	0.66 kg
MZ00ESM	D228761	Electronic System Monitor ESM size 00 for MULTIVERT®160 A with cabling of instrument leads	1 piece	0.35 kg
1.000.852	Q1002285	indicator for switch door position micro switch, 1 change-over contact 5 A, 250 V	1 piece	90 g


MULTIVERT[®] MULTIBLOC[®]

ACCESSORIES



1.000.107

1.000.101



Catalog number	ltem number	Design	Package	Weight
1.000.106	R1023285	size 00, 100 A, with drag indicator, triple pole measurement (optional L1, L2, L3)	1 piece	0.34 kg
1.000.107	S1023286	size 00, 150 A, with drag indicator, triple pole measurement (optional L1, L2, L3)	1 piece	0.34 kg
1.000.100	K1023279	size 00, 100 A, with drag indicator, single pole measurement	1 piece	0.34 kg
1.000.101	L1023280	size 00, 150 A, with drag indicator, single pole measurement	1 piece	0.34 kg



Labelling facilities

Amperemeter units

Catalog number	ltem number	Design	Package	Weight
MZ00BT2	K215611	label holder size 00	1 piece	10 g



00SZS

00SZESK



1.003.433



00SZVK1



1.000.098

Varieties of cable termination

Catalog number	ltem number	Design	Package	Weight
00SZS	M229298	M8 terminal screw for switch gear size 00 1 set = 3 pieces	1 set	35 g
00SZESK	E214594	clamp strap Cu 4–70 mm² for switch gear size 00 1 set = 3 pieces	1 set	35 g
00SZA70	R211523	Al/Cu clamp 1,5–70 mm² for switch gear size 00 1 set = 3 pieces	1 set	75 g
1.003.571	V1033684	Al/Cu clamp 50 -95 mm ² round stranded for switch gear size 00 1 set = 3 pieces	1 set	88 g
1.003.433	L1022958	triple clamp per pole 1.5 up to 16 mm ² 1 set = 3 pieces	1 set	0.14 kg
00SZVK1	D1023434	V-terminal clamp size 00, 10–70 mm ² round stranded, 10-95 mm ² round solid, 35–95 mm ² single stranded, 50–95 mm ² single solid, M = 12 Nm	30	0.4 kg
1.000.098	E1023435	insulation cap for V-terminal clamp size 00	12/120	2 g

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.



131



numbe

component

1.000.900 F1002184 3 M8 terminal screws

MULTIVERT® 160A

PRODUCT RANGE

Package

Weight

1 piece 1.12 kg

Size 00, 690VAC, Triple Pole Switching



1.000.900 1.000.903



1.000.901 X1023129 3 clamp straps Cu 4-70 mm² with cover shroud MZ00KH 1 piece 1.12 kg 1.000.902 Z1023131 3 Al/Cu clamps 1,5-70 mm² with cover shroud MZ00KH 1 piece 1.12 kg with V-terminal for A1023132 with cover shroud 1.000.915 1.000.903 1 piece 1.12 kg V-terminal clamps size 00 1.000.904 B1023133 3 frame clamps Cu 2,5-70 mm² with cover shroud MZ00KH 1 piece 1.1 kg MULTIVERT® 1.000.900 with cabling of 1.000.905 G1002185 3 M8 terminal screws 1 piece 1.47 kg instrument leads MULTIVERT® 1.000.901 with cabling of 1.000.906 C1023134 3 clamp straps Cu 4-70 mm² 1 piece 1.47 kg instrument leads MULTIVERT® 1.000.902 with cabling of 1.000.907 D1023135 3 Al/Cu clamps 1,5-70 mm² 1 piece 1.47 kg instrument leads MULTIVERT® 1.000.903 with cabling of with V-terminal 1.000.908 E1023136 1 piece 1.47 kg for V-terminal clamps size 00 instrument leads MULTIVERT® 1.000.904 with cabling of 1.18 kg 1.002.437 Y1023130 3 frame clamps Cu 2,5-70 mm² 1 piece instrument leads

with cover shroud MZ00KH

MULTIVERT® 160 A size 00 100 mm bus bar system 1 x triple pole switching

1.000.905



MULTIVERT® 160 A size 00 185 mm bus bar system 1 x triple pole switching

Catalog number	ltem number	Cable termination components	Design	Package	Weight
1.001.339	Y1023153	3 M8 terminal screws	including adjustment cover art.no. MZ00AAD and adapter 1.001.298	1 piece	1.8 kg

1.001.339

ACCESSORIES



MZ00KH

Cover/shrouds for cable termination

Catalog number	ltem number	Design	Package	Weight
MZ00KH	F1023298	cover shroud length 106 mm for MULTIVERT®/BSL 160 A	1 piece	20 g
MZ00KA	L1023464	extended cover shroud for cover shroud MZ00KH	1 piece	40 g
1.000.915	H1023300	cover shroud for MULTIVERT®/BSL 160 A with V-terminal	1 piece	50 g

ACCESSORIES

Size 00, 690VAC, Triple Pole Switching





Catalog number	ltem number	Design	Package	Weight
MZ00AAD	X214081	2 piece adjustment, with integrated area for labeling to adapt to MULTIVERT® for 185 mm bus bar system	1 set	0.1 kg
MZAW	D218687	support angle for support of cover plate 1 set = 4 pieces	1 set	27 g



MZ01LPAP 1.002.493

Covers/spare way covers

Catalog number	ltem number	Design	Application	Package	Weight
MZ00LPAP	B1023409	spare way cover without level adjustment width 50 mm, length 320 mm for single adapter MZ00ESA and double adapter MZ00DSA including fixing material	bus bar system 100 mm	1 piece	50 g
MZ01LPAP	C1023410	spare way cover without level adjustment width 50 mm, length 500 mm including fixing material	bus bar system 185 mm	1 piece	60 g
1.002.493	N1002283	spare way cover width 50 mm, length 630 mm for covering of open installation spaces in distribution units with central cover	bus bar system 185 mm	1 piece	0.14 kg
1.002.830	E1023412	spare way cover width 50 mm, length 630 mm with level adjustment 123 mm for bus bar installation, set = cover + fixing set (2 distance pieces, 2 screw rivets)	bus bar system 185 mm	1 set	0.20 kg



1.002.830



C

1.002.646

Installation devices/bus bar installation

Catalog number	ltem number	Design	Package	Weight
00SZRK3	K215105	hooked clamp size 00, M = 5 Nm 1 set = 3 pieces	1 set	0.10 kg
1.002.646	W1023450	M10 insert nut, size 00 1 set = 30 pieces	1 set	0.12 kg

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.



MULTIVERT[®] MULTIBLOC[®]

ACCESSORIES

Size 00, 690VAC, Triple Pole Switching



1.001.289



MZ00DSA MZ00ESA MZ00ESAE-CO





Adapter für installation on to bus bars with clamp terminal

Catalog number	ltem number	Design	Application	Package	Weight
1.001.289	C1023295	single adapter 100/185 mm with increased touch protection to obtain uniform profile in height for combined installation with MULTIVERT 250 A, 400 A, 630 A	MULTIVERT® 160 A/100 mm 1x3-pole	1 piece	0.56 kg
1.001.298	Y1023291	double adapter 100/185 mm with increased touch protection to obtain uniform profile in height for combined installation with MULTIVERT 250 A, 400 A, 630 A	MULTIVERT [®] 160 A/100 mm 1x3-pole	1 piece	0.8 kg

Adapter für installation on to bus bars with screw terminal

Catalog number	Item number	Design	Application	Package	Weight
MZ00DSA	C217145	double adapter 100/185 mm with increased touch protection to obtain uniform profile in height for combined installation with MULTIVERT®/BSL 250 A, 400 A, 630 A	MULTIVERT® 160 A/100 mm 1x3-pole	1 piece	0.71 kg
MZ00ESA	Q216628	single adapter 100/185 mm with increased touch protection to obtain uniform profile in height for combined installation with MULTIVERT®/BSL 250 A, 400 A, 630 A	MULTIVERT® 160 A/100 mm 1x3-pole	1 piece	0.51 kg
MZ00ESAECO	D1023296	Single adapter 100/185 mm to obtain uniform profile in height for combined installation with MULTIVERT®/BSL 250 A, 400 A, 630 A	MULTIVERT [®] 160 A/100 mm 1x3-pole	1 piece	0.19 kg

Indication facilities

Catalog number	ltem number	Design	Package	Weight
1.002.939	Y1023452	electronic fuse monitoring ESÜ size 00 for MULTIVERT® 160 A with cabling of instrument leads (rated voltage 525VAC)	1 piece	0.66 kg
MZ00ESM	D228761	Electronic System Monitor ESM size 00 for MULTIVERT®160 A with cabling of instrument leads	1 piece	0.35 kg
1.000.852	Q1002285	indicator for switch door position micro switch, 1 change-over contact 5 A, 250 V	1 piece	90 g



ACCESSORIES

Size 00, 690VAC, Triple Pole Switching





Amperemeter units

Catalog number	ltem number	Design	Package	Weight
1.000.106	R1023285	size 00, 100 A, with drag indicator, triple pole measurement (optional L1, L2, L3)	1 piece	0.34 kg
1.000.107	S1023286	size 00, 150 A, with drag indicator, triple pole measurement (optional L1, L2, L3)	1 piece	0.34 kg
1.000.100	K1023279	size 00, 100 A, with drag indicator, single pole measurement	1 piece	0.34 kg
1.000.101	L1023280	size 00, 150 A, with drag indicator, single pole measurement	1 piece	0.34 kg



1.000.119+ 1.000.123

1.000.120 + 1.000.124

Catalog number	ltem number	Design	Package	Weight
1.000.121	no. 1.000.125 for level adjustment, 1 piece installed, 2 pieces additionally packed 1.000.123 current transformer for adapter for single pole measurement up to 150/5A, class 1 set = 1 piece current transformer + 3 pieces distance tubes art. no. 1.000.125 for level adjustment, 1 piece installed, 2 pieces additionally packed current transformer for adapter for triple pole measurement up to 150/5A, class 1		1 set	0.51 kg
1.000.123			1 set	0.52 kg
1.000.122			1 set	0.78 kg
1.000.124	J1024612	current transformer for adapter for triple pole measurement up to 150/5A, class 1 set = 3 pieces current transformer with distance tubes art.no. 1.000.125 for level adjustment 3 pieces installed	1 set	0.81 kg
1.000.125	V1024599	distance tube for adapter for level adjustment supplementary set for neighbouring MULTIVERT [®] without measurement to obtain uniform profile in height 1 set = 3 pieces	1 set	0.37 kg
1.000.117	R1023446	single adapter 100/185 mm for circuit transformer	1 piece	0.34 kg
1.000.119	A1023293	double adapter 100/185 mm for circuit transformer	1 piece	0.58 kg
1.000.120	B1023294	double adapter 185/185 mm for circuit transformer	1 piece	0.56 kg



MULTIVERT[®] MULTIBLOC[®]

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.

Mers

Expertise, our sourc

A

ACCESSORIES

Size 00, 690VAC, Triple Pole Switching

Current transformers/external current transformers

637	
MZ003SW100	



SZ1SW150



MZ00PR150

Catalog number	Item number	Design	Package	Weight
MZ001SW100	MZ001SW100 C1024606 current transformer up to 100 A for single pole measurement between bus bar and MULTIVERT® MZ001SW100 C1024606 set = 1 piece current transformer + 3 pieces distance tubes for level adjustment, 1 piece installed in the current transformer, 2 pieces additionally packed		1 set	0.55 kg
MZ001SW150	MZ001SW150 E1024608 Current transformer up to 150 A for single pole measurement between bus bar and MULTIVERT [®] set = 1 piece current transformer + 3 pieces distance tubes for level adjustment, 1 piece installed in the current transformer, 2 pieces additionally packed		1 set	0.55 kg
MZ003SW100	MZ003SW100 B1024605 Current transformer up to 100/5A for triple pole measurement between bus bar and MULTIVERT®, class 1 set = 3 pieces current transformer with distance tubes for level adjustment, 3 pieces installed in the current trans- former		1 set	1.84 kg
MZ003SW150	D1024607	current transformer up to 150/5A for triple pole measurement between bus bar and MULTIVERT®, class 1 set = 3 pieces current transformer with distance tubes for level adjustment, 3 pieces installed in the current trans- former	1 set	1.85 kg
SZ1SW100	H1024565	current transformer up to 100/5A for single pole measurement between bus bars, class 1 (incoming and outgoing bar)	1 piece	0.32 kg
SZ1SW150	J1024566	current transformer up to 150/5A for single pole measurement between bus bars, class 1 (incoming and outgoing bar)	1 piece	0.33 kg
MZ00PR150 R1024596 R1024596 distance tube for level adjustment, up to 150/5A, supplementary set for neighbouring MULTIVERT® without measurement to obtain uniform profile in height 1 set = 3 pieces		1 set	0.4 kg	



Labelling facilities

Catalog number	ltem number	Design	Package	Weight
MZ00BT2	K215611	label holder size 00	1 piece	10 g



Size 00, 690VAC, Triple Pole Switching





1.003.433



00SZVK1



1.000.098

Catalog number	ltem number	Design	Package	Weight
00SZS	00SZS M229298 M8 terminal screw for switch gear size 00 1 set = 3 pieces		1 set	35 g
00SZESK	E214594	clamp strap Cu 4–70 mm² for switch gear size 00 1 set = 3 pieces	1 set	35 g
00SZA70	R211523	Al/Cu clamp 1,5–70 mm² for switch gear size 00 1 set = 3 pieces	1 set	75 g
1.003.571	V1033684	Al/Cu clamp 50 -95 mm ² round stranded for switch gear size 00 1 set = 3 pieces	1 set	88 g
1.003.433	L1022958	triple clamp per pole 1.5 up to 16 mm ² 1 set = 3 pieces	1 set	140 g
00SZVK1	D1023434	V-terminal clamp size 00, 10–70 mm ² round stranded, 10-95 mm ² round solid, 35–95 mm ² single stranded, 50–95 mm ² single solid, M = 12 Nm	30	400 g
1.000.098	E1023435	insulation cap for V-terminal clamp size 00	12/120	2 g

e Switching Varieties of cable termination

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.



ACCESSORIES

PRODUCT RANGE

Size 00, 690VAC, single pole switching

MULTIVERT[®] 160 A size 00 185 mm 3 x single pole switching



Catalog number	ltem number	Cable termination components	Design	Package	Weight
M01N0G	Y228756	3 M8 terminal screws	with cover shroud MZ00KH	1 piece	1.9 kg
M01S0G	X1023152	3 clamp straps Cu 4-70 mm ²	with cover shroud MZ00KH	1 piece	1.9 kg
M01A0G	Q1023146	3 Al/Cu clamps 1,5-70 mm ²	with cover shroud MZ00KH	1 piece	1.9 kg
1.000.910	G1023138	with V-terminal for V-terminal clamps size 00	with cover shroud 1.000.915	1 piece	1.9 kg
1.001.725	M1023143	V-terminal with 3 V-terminal clamps size 00	with cover shroud 1.000.915	1 piece	1.1 kg
M01N0E11G	R1023147	3 M8 terminal screws	MULTIVERT [®] M01N0G with cabling of instrument leads	1 piece	2.25 kg
M01S0E11G	W1023151	3 clamp straps Cu 4-70 mm ²	MULTIVERT [®] M01S0G with cabling of instrument leads	1 piece	2.25 kg
M01A0E11G	P1023145	3 Al/Cu clamps 1,5-70 mm ²	MULTIVERT [®] M01A0G with cabling of instrument leads	1 piece	2.25 kg
1.000.911	L1023142	with V-terminal for V-terminal clamps size 00	MULTIVERT® 1.000.910 with cabling of instrument leads	1 piece	2.25 kg

M01N0G 1.001.725



1.002.939

M01N0E11G



Size 00, 690VAC, single pole switching



MZ00KH



Cover/shrouds for cable termination

Catalog number	ltem number	Design	Package	Weight
MZ00KH	F1023298	cover shroud length 106 mm for MULTIVERT®/BSL 160 A	1 piece	20 g
MZ00KA	L1023464	extended cover shroud for cover shroud MZ00KH	1 piece	40 g
1.000.915	H1023300	cover shroud for MULTIVERT®/BSL 160 A with V-terminal	1 piece	50 g
MZ00KAD	G1023299	cover shroud length 156 mm for MULTIVERT®/BSL 160 A	1 piece	60 g

Weight

10 g

27 g

1 piece

1 set

ACCESSORIES



MZ01AS

MZAW

Catalog number

MZ01AS

MZAW



MZ01LPAP

00SZRK3

1.002.493

1.002.830

1.002.646

Installation devices/bus bar installation

Catalog number	ltem number	Design	Package	Weight
00SZRK3	K215105	hooked clamp size 00, M = 5 Nm 1 set = 3 pieces	1 set	100 g
1.002.646	W1023450	M10 insert nut, size 00 1 set = 30 pieces	1 set	120 g

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.



1 set = 4 pieces

F228763

D218687

Covers/spare way covers

Covers/level & system adjustment covers

terminal)

Catalog number	Item number Design		Application	Package	Weight
MZ01LPAP	C1023410	spare way cover without level adjustment width 50 mm, length 500 mm including fixing material	bus bar system 185 mm	1 piece 60 g	
1.002.493	N1002283	spare way cover width 50 mm, length 630 mm for covering of open installation spaces in distribution units with central cover	bus bar system 185 mm	1 piece	140 g
1.002.830	E1023412	spare way cover width 50 mm, length 630 mm with level adjustment 123 mm for bus bar installation, set = cover + fixing set (2 distance pieces, 2 screw rivets)	bus bar system 185 mm	1 set	200 g

adjustment to adapt to MULTIVERT® 250 A, 400 A, 630 A (top

support angle for support of cover plate

Catalog number

MZ01DSA G228764

MZ01ESA H228765

Indication facilities

M1023442

MULTIVERT® 160A/185mm

Size 00, 690VAC, single pole switching



Adapter für installation on to bus bars with clamp terminal

Adapter für installation on to bus bars with screw terminal

double adapter 185/185 mm

for combined installation with

single adapter 185/185 mm (for installation of MULTIVERT®/BSL

with screws M8)

with increased touch protection

to obtain uniform profile in height

to obtain uniform profile in height

for combined installation with MULTIVERT®/BSL 250 A, 400 A, 630 A

MULTIVERT®/BSL 250 A, 400 A, 630 A

Catalog number	ltem number	Design	Application	Package	Weight
1.001.300	Z1023292	double adapter 185/185 mm with increased touch protection to obtain uniform profile in height for combined installation with MULTIVERT 250 A, 400 A, 630 A	MULTIVERT® 160 A/185 mm 3x1-pole	1 piece	0.75 kg






MZ01DSA MZ01ESA



1.002.939



Catalog
numberItem numberDesign1.002.939Y1023452electronic fuse monitoring ESÜ size 00 for MULTIVERT®160 A
with cabling of instrument leads (rated voltage 525VAC)MZ00ESMD228761Electronic System Monitor ESM size 00
for MULTIVERT®160 A with cabling of instrument leads

indicator for switch door position 1 "a" contact/ 1 "b" contact, 5 A, 250 V

3 x single pole switching

for MULTIVERT® 160 A/bus bar system 185 mm

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.

MZHD

ACCESSORIES

Package

1 piece 0.7 kg

1 piece 0.39 kg

0.66 kg

0.35 kg

1 piece 0.01 kg

1 piece

1 piece

MULTIVERT®

160 A/185 mm

MULTIVERT[®]

160 A/185 mm

1x3-pole

1x3-pole

140	



Size 00, 690VAC, single pole switching







Amperemeter units

Catalog number	V Item number Design		Package	Weight
1.000.106 R1023285 size 00, 100 A, with drag indicator, triple pole measure (optional L1, L2, L3)		size 00, 100 A, with drag indicator, triple pole measurement (optional L1, L2, L3)	1 piece	0.34 kg
1.000.107	S1023286	size 00, 150 A, with drag indicator, triple pole measurement (optional L1, L2, L3)	1 piece	0.34 kg
1.000.100	1.000.100 K1023279 size 00, 100 A, with drag indicator, single pole measurement		1 piece	0.34 kg
1.000.101 L1023280 size 00, 150 A		size 00, 150 A, with drag indicator, single pole measurement	1 piece	0.34 kg

Current transformers in combination with adaper

Catalog number	ltem number	Design		Weight
1.000.121	F1024609	current transformer for adapter for single pole measurement up to 100/5A, class 1 set = 1 piece current transformer + 3 pieces distance tubes art. no. 1.000.125 for level adjustment, 1 piece installed, 2 pieces additionally packed	1 set	0.51 kg
1.000.123	1.000.123 H1024611 current transformer for adapter for single pole measurement up to 150/5A, class 1 set = 1 piece current transformer + 3 pieces distance tubes art. no. 1.000.125 for level adjustment, 1 piece installed, 2 pieces additionally packed		1 set	0.52 kg
1.000.122 G1024610 current transformer for adapt for triple pole measurement i set = 3 pieces current transformer for adapt 1.000.125 for level adjustme 1.000.124 J1024612 current transformer for adapt for triple pole measurement i set = 3 pieces current transformer for adapt for triple pole measurement set = 3 pieces current transformer for adapt for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 pieces current transformer for triple pole measurement i set = 3 p		current transformer for adapter for triple pole measurement up to 100/5A, class 1 set = 3 pieces current transformer with distance tubes art.no. 1.000.125 for level adjustment 3 pieces installed	1 set	0.78 kg
		current transformer for adapter for triple pole measurement up to 150/5A, class 1 set = 3 pieces current transformer with distance tubes art.no. 1.000.125 for level adjustment 3 pieces installed	1 set	0.81 kg
1.000.125	1.000.125 V1024599 distance tube for adapter for level adjustment supplementary set for neighbouring MULTIVERT® without measurement to obtain uniform profile in height 1 set = 3 pieces		1 set	0.37 kg
1.000.117	R1023446	single adapter 100/185 mm for circuit transformer	1 piece	0.34 kg
1.000.119	A1023293	double adapter 100/185 mm for circuit transformer	1 piece	0.58 kg
1.000.120	B1023294	double adapter 185/185 mm for circuit transformer	1 piece	0.56 kg

1.000.119+ 1.000.123

1.000.120 + 1.000.124

MERSEN reserves the right to change, update or correct, without notice, any information contained in this datasheet.



ACCESSORIES

ACCESSORIES

Size 00, 690VAC, single pole switching

Current transformers/external current transformers

MZ003SW100	
6	

A

SZ1SW150



MZ00PR150

Catalog number	Item number	Design	Package	Weight
MZ001SW100 C1024606		current transformer up to 100 A for single pole measurement between bus bar and MULTIVERT [®] set = 1 piece current transformer + 3 pieces distance tubes for level adjustment, 1 piece installed in the current trans- former, 2 pieces additionally packed	1 set	0.55 kg
MZ001SW150 E1024608		current transformer up to 150 A for single pole measurement between bus bar and MULTIVERT [®] set = 1 piece current transformer + 3 pieces distance tubes for level adjustment, 1 piece installed in the current transformer, 2 pieces additionally packed	1 set	0.55 kg
MZ003SW100	B1024605	current transformer up to 100/5A for triple pole measurement between bus bar and MULTIVERT®, class 1 set = 3 pieces current transformer with distance tubes for level adjustment, 3 pieces installed in the current trans- former	1 set	1.84 kg
MZ003SW150 D1024607		current transformer up to 150/5A for triple pole measurement between bus bar and MULTIVERT®, class 1 set = 3 pieces current transformer with distance tubes for level adjustment, 3 pieces installed in the current trans- former	1 set	1.85 kg
SZ1SW100	H1024565	current transformer up to 100/5A for single pole measurement between bus bars, class 1 (incoming and outgoing bar)	1 piece	0.32 kg
SZ1SW150	J1024566	current transformer up to 150/5A for single pole measurement between bus bars, class 1 (incoming and outgoing bar)	1 piece	0.33 kg
MZ00PR150 R1024596 distance supplementation measure		distance tube for level adjustment, up to 150/5A, supplementary set for neighbouring MULTIVERT® without measurement to obtain uniform profile in height 1 set = 3 pieces	1 set	0.4 kg



Labelling facilities

Catalog number	ltem number	Design	Package	Weight
MZ00BT2	K215611	label holder size 00	1 piece	10 g



Size 00, 690VAC, single pole switching



1.003.433



1.000.098

Catalog number	ltem number	Design	Package	Weight
00SZS	M229298	M8 terminal screw for switch gear size 00 1 set = 3 pieces	1 set	35 g
00SZESK	E214594	clamp strap Cu 4–70 mm² for switch gear size 00 1 set = 3 pieces	1 set	35 g
00SZA70	R211523	Al/Cu clamp 1,5–70 mm² for switch gear size 00 1 set = 3 pieces	1 set	75 g
1.003.571	V1033684	Al/Cu clamp 50 -95 mm ² round stranded for switch gear size 00 1 set = 3 pieces	1 set	88 g
1.003.433	L1022958	triple clamp per pole 1.5 up to 16 mm² 1 set = 3 pieces	1 set	140 g
00SZVK1	D1023434	V-terminal clamp size 00, 10–70 mm ² round stranded, 10-95 mm ² round solid, 35–95 mm ² single stranded, 50–95 mm ² single solid, M = 12 Nm	30	400 g
1.000.098	E1023435	insulation cap for V-terminal clamp size 00	12/120	2 g

MULTIVERT® 250A

Size 1, 690VAC

PRODUCT RANGE

ACCESSORIES



MULTIVERT[®] 250 A size 1 185 mm 3 x single pole switching

Varieties of cable termination

Catalog number	ltem number	Cable termination components	Design	Package	Weight
1.100.000	H1002186	3 M10 bolts	-	1 piece	4.52 kg
1.110.000	J1023163	3 M10 insert nuts	-	1 piece	4.46 kg
1.120.000	K1023164	V-terminal for V-ter- minal clamps size 1,2,3	-	1 piece	4.38 kg
1.120.900	Q1023169	V-terminal, 2 terminals per phase for V-terminal clamps size 1,2,3	-	1 piece	5.5 kg
1.100.083	N1023167	3 M10 bolts	MULTIVERT [®] 1.100.000 with integrated C.T. 250/5A, 3,75 VA, class 1 for single pole measurement (ready fitted in pole 1)	1 piece	4.6 kg
1.100.062	L1023165	3 M10 bolts	MULTIVERT [®] 1.100.000 with integrated C.T. 250/5A, 3,75 VA, class 0,5; calibrated, for single pole measurement (ready fitted in pole 1)	1 piece	4.6 kg
1.100.093	P1023168	3 M10 bolts	MULTIVERT® 1.100.000 with integrated C.T. 250/5A, 3,50 VA, class 1 for triple pole measurement	1 piece	5.3 kg
1.100.072	M1023166	3 M10 bolts	MULTIVERT® 1.100.000 with integrated C.T. 250/5A, 3,50 VA, class 0,5; calibrated, for triple pole measurement	1 piece	4.6 kg

