

Productname : SCREEN TFT  
 Ref.Nr.: BDS001400\_3\_20181115 (EN)

Creationdate : 15.11.18 Version : 4.1  
 Replaces: BDS001400\_20170629

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**SCREEN TFT**  
 Aerosol

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Precision

### 1.3. Details of the supplier of the safety data sheet

**CRC Industries Europe bvba**  
 Touwslagerstraat 1  
 9240 Zele  
 Belgium  
 Tel.: +32(0)52/45.60.11  
 Fax.: +32(0)52/45.00.34  
 E-mail : hse@crcind.com

Subsidiaries		Tel	Fax
CRC Industries Finland Oy	Smedsgatan 3-5 LT4, PL62, 08101 LOJO	+358/(19)32.921	
CRC Industries France	6, avenue du marais, C.S. 90028, 95102 Argenteuil Cedex	01.34.11.20.00	01.34.11.09.96
CRC Industries Deutschland GmbH	Südring 9, D-76473 Iffezheim	(07229) 303 0	(07229)30 32 66
CRC INDUSTRIES IBERIA S.L.U.	GREMIO DEL CUERO-PARC.96, POLIGONO INDUSTRI. DE HONTORIA, 40195 SEGOVIA	0034/921.427.546	0034/921.436.270
CRC Industries Sweden	Laxfiskevägen 16, 433 38 Partille	0046/31 706 84 80	0046/31 27 39 91

### 1.4. Emergency telephone number

CRC Industries Europe, Belgium: Tel.: +32(0)52/45.60.11 (office hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

**Physical:** Aerosol, category 3  
 Pressurised container: May burst if heated.



**Productname :** SCREEN TFT  
**Ref.Nr.:** BDS001400\_3\_20181115 (EN)  
**Creationdate :** 15.11.18 Version : 4.1  
**Replaces:** BDS001400\_20170629

Not flammable under normal conditions of use but contains flammable components  
 (Testing on flammability in closed space, FEA X610-E, are negative)

Classification is based on test data.

**Health:** Not classified

Classification based on calculation method.

**Environment:** Not classified

Classification based on calculation method.

## 2.2. Label elements

### Labelling according to Regulation (EC) No 1272/2008

<b>Signal word:</b>	Warning
<b>Hazard statement(s):</b>	H229 : Pressurised container: May burst if heated.
<b>Precautionary statement(s):</b>	P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 : Do not pierce or burn, even after use. P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Supplemental Hazard information:</b>	3 % by mass of the contents are flammable. Contains: 1,2-benzisothiazol-3(2H)-one May produce an allergic reaction.

**Regulation (EC) No 648/2004 on detergents:** aliphatic hydrocarbons < 5 %  
benzisothiazolinone, benzoic acid

## 2.3. Other hazards

No information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable.

### 3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	01-2119485926-20	68512-91-4	270-990-9	1-5	Press. Gas, Flam. Gas 1	H280,H220	K,G



**Productname :** SCREEN TFT  
**Ref.Nr.:** BDS001400\_3\_20181115 (EN)

**Creationdate :** 15.11.18 Version : 4.1  
**Replaces:** BDS001400\_20170629

Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides	01-2119490061-47	308062-28-4	(931-292-6)	<0.1	Eye Dam. 1, Acute Tox. 4, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic 2	H318,H302,H315,H400,H411	Q
5-chloro-2-methyl-2H-isothiazol-3-one	-	26172-55-4	247-500-7	<0.1	Acute Tox. 2, Acute Tox. 2, Acute Tox. 2, Skin Corr. 1B, Skin Sens. 1, Eye Dam. 1, Aquatic Acute 1	H300,H310,H330,H314,H317,H318,H400	R
2-methyl-2H-isothiazol-3-one	01-2120764690-50	2682-20-4	220-239-6	<0.1	Acute Tox. 3, Acute Tox. 3, Acute Tox. 2, Skin Corr. 1B, Skin Sens. 1, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1	H301,H311,H330,H314,H317,H400,H410	M,X
Benzoic acid	01-2119455536-33	65-85-0	200-618-2	<0.1	STOT RE 1, Skin Irrit. 2, Eye Dam. 1	H372,H315,H318	
sodium salt of an alkyl ether sulfate2	01-2119488639-16	-	500-234-8 (NLP)	<0.1	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3	H315,H318,H412	X
Sulfonic acids, C14-17-sec-alkane, sodium salts	01-2119489924-20	97489-15-1	307-055-2	<0.1	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 3	H302,H315,H318,H412	
Disodium metasilicate anhydrous	01-2119449811-37	6834-92-0	229-912-9	<0.1	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3	H290,H314,H335	
1,2-benzisothiazol-3(2H)-one	-	2634-33-5	220-120-9	<0.05	Acute Tox. 2, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 2	H330,H302,H315,H319,H317,H400,H411	X,R

**Explanation notes**

G : exempted from the obligation to register in accordance with art.2(7)of REACH Regulation No 1907/2006

K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)

M : M acute = 10

Q : The CAS-no is only an indicative identifier to be used outside the EU for global inventory entries.

R : substance in plant protection or biocidal product regarded as being registered (art.15 REACH Regulation No 1907/2006)

X : SCL (specific concentration limit)in accordance with art.10 of CLP Regulation No 1272/2008

(\* Explanation phrases : see chapter 16)

**SECTION 4: First aid measures****4.1. Description of first aid measures**

<b>Contact with eyes :</b>	If substance has got into eyes, immediately wash out with plenty of water
<b>Contact with skin :</b>	Wash with plenty of soap and water.
<b>Inhalation :</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
<b>Ingestion :</b>	If swallowed accidentally, do not induce vomiting and seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

**CRC Industries Europe bvba**

Touwslagerstraat 1, 9240 Zele – Belgium

Tel (+32) (0) 52 / 45 60 11 – Fax (+32) (0) 52 / 45 00 34 – www.crcind.com

**3 / 10**

**Productname :** SCREEN TFT  
**Ref.Nr.:** BDS001400\_3\_20181115 (EN)

**Creationdate :** 15.11.18 Version : 4.1  
**Replaces:** BDS001400\_20170629

**Inhalation :** No adverse health effects expected  
**Ingestion :** May cause gastrointestinal disturbances  
Symptoms : sore throat, abdominal pain, nausea, vomiting  
**Skin contact :** May cause irritation.  
**Eye contact :** May cause irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**General Advice :** In case of accident or if you feel unwell, seek medical advice (show the label where possible)  
If symptoms persist always call a doctor

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

water, foam, carbon dioxide or dry agent

#### 5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C  
Forms hazardous decomposition products  
CO,CO2

#### 5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water  
In case of fire, do not breathe fumes

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing and gloves.

#### 6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

#### 6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material  
Wash spill site with water and detergent



**Productname :** SCREEN TFT  
**Ref.Nr.:** BDS001400\_3\_20181115 (EN)

**Creationdate :** 15.11.18 Version : 4.1  
**Replaces:** BDS001400\_20170629

#### 6.4. Reference to other sections

For further information see section 8

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Keep away from heat and sources of ignition  
Do not spray on a naked flame or incandescent material.  
Do not pierce or burn aerosols, even after use.  
Do not breathe aerosols or vapours.  
Ensure adequate ventilation  
Avoid contact with skin and eyes.

#### 7.2. Conditions for safe storage, including any incompatibilities

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Store in a well-ventilated place.  
Store frost free  
Keep out of reach of children.

#### 7.3. Specific end use(s)

Cleaners - Precision

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits :

No information available

#### 8.2. Exposure controls

<b>Control procedures :</b>	Ensure adequate ventilation Keep away from heat and sources of ignition
<b>Personal protection :</b>	Take precautions to avoid contact with skin and eyes when handling the product. Ensure adequate ventilation
<b>inhalation :</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>hands and skin :</b>	For incidental contact with the product wear chemical-resistant gloves (standard EN 374). The use of disposable gloves is acceptable provided that they are changed immediately after a splash or spill.



**Productname :** SCREEN TFT  
**Ref.Nr.:** BDS001400\_3\_20181115 (EN)  
**Creationdate :** 15.11.18 Version : 4.1  
**Replaces:** BDS001400\_20170629

In all cases handle and use the product in accordance with good industrial hygiene practices.

**Recommended gloves:** (neoprene)

**eyes :** Wear safety eyewear according to EN 166.

**Environmental protection:** Avoid release to the environment.  
Collect spillage.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

**Apperance : physical state :** Propane/butane propelled liquid.  
**colour :** Colorless.  
**odour :** Odorless.  
**pH :** 9 - 10  
**Boiling point/range :** Not applicable.  
**Flash point :** None  
**Evaporation rate :** Not applicable.  
**Explosion limits : upper limit :** Not applicable.  
**lower limit :** Not applicable.  
**Vapour pressure :** Not available.  
**Relative density :** 1.0 g/cm<sup>3</sup> (@ 20°C).  
**Solubility in water :** Soluble in water  
**Auto-ignition :** > 200 °C  
**Viscosity :** Not applicable.

### 9.2. Other information

**VOC = volatile organic compounds** 35 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purpose

### 10.2. Chemical stability

Stable

### 10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose



Productname : SCREEN TFT  
Ref.Nr.: BDS001400\_3\_20181115 (EN)

Creationdate : 15.11.18 Version : 4.1  
Replaces: BDS001400\_20170629

#### 10.4. Conditions to avoid

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.  
Avoid overheating  
Store frost free

#### 10.5. Incompatible materials

Strong oxidising agent

#### 10.6. Hazardous decomposition products

CO,CO2

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**acute toxicity:** based on available data the classification criteria are not met  
**skin corrosion/irritation:** based on available data the classification criteria are not met  
**serious eye damage/irritation:** based on available data the classification criteria are not met  
**respiratory or skin sensitisation:** based on available data the classification criteria are not met  
**germ cell mutagenicity:** based on available data the classification criteria are not met  
**carcinogenicity:** based on available data the classification criteria are not met  
**toxicity for reproduction:** based on available data the classification criteria are not met  
**STOT-single exposure:** based on available data the classification criteria are not met  
**STOT repeated exposure:** based on available data the classification criteria are not met  
**aspiration hazard:** based on available data the classification criteria are not met

#### Information on likely routes of exposure:

**Inhalation :** No adverse health effects expected  
**Ingestion :** Ingestion is unlikely to occur  
**Skin contact :** May cause irritation.  
**Eye contact :** May cause irritation.

#### Toxicological data :

Hazardous ingredient	CAS-nr.	method	
Disodium metasilicate anhydrous	6834-92-0	LD50 oral rat	300-2000 mg/kg
		LC50 inhal.rat	1-5 mg/l
		LD50 derm.rat	>2000 mg/kg
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	308062-28-4	LD50 oral rat	1064 mg/kg

Productname : SCREEN TFT  
Ref.Nr.: BDS001400\_3\_20181115 (EN)

Creationdate : 15.11.18 Version : 4.1  
Replaces: BDS001400\_20170629

## SECTION 12: Ecological information

### 12.1. Toxicity

Not classified

### Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
Disodium metasilicate anhydrous	6834-92-0	IC50 algae	207 mg/l
		LC50 fish	210 mg/l
		EC50 daphnia	1700 mg/l
Amines, C12-14 (even numbered)- alkyldimethyl, N-oxides	308062-28-4	IC50 algae	0.143 mg/l
		LC50 fish	2.67 mg/l
		EC50 daphnia	3.1 mg/l

### 12.2. Persistence and degradability

No experimental data available

### 12.3. Bioaccumulative potential

No experimental data available

### 12.4. Mobility in soil

Soluble in water

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No experimental data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Product :** This material and its container must be disposed of in a safe way. Do not discharge into drains or the environment, dispose to an authorised waste collection point.

**National regulations :** Disposal should be in accordance with local, state or national legislation





Productname : SCREEN TFT  
Ref.Nr.: BDS001400\_3\_20181115 (EN)

Creationdate : 15.11.18 Version : 4.1  
Replaces: BDS001400\_20170629

## SECTION 14: Transport information

### 14.1. UN number

UN-number : 1950

### 14.2. UN proper shipping name

Proper shipping name: AEROSOLS

### 14.3. Transport hazard class(es)

Class: 2.2  
ADR/RID - Classification code: 5A

### 14.4. Packing group

Packing group: Not applicable.

### 14.5. Environmental hazards

ADR/RID - Environmentally hazardous: No  
IMDG - Marine pollutant: No  
IATA/ICAO - Environmentally hazardous: No

### 14.6. Special precautions for user

ADR/RID - Tunnelcode: (E)  
IMDG - Ems: F-D, S-U  
IATA/ICAO - PAX: 203  
IATA/ICAO - CAO: 203

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.  
Regulation (EC) No 1907/2006 (REACH)  
Regulation (EC) No 1272/2008 (CLP)



**Productname :** SCREEN TFT  
**Ref.Nr.:** BDS001400\_3\_20181115 (EN)  
**Creationdate :** 15.11.18 Version : 4.1  
**Replaces:** BDS001400\_20170629

Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

## 15.2. Chemical safety assessment

No information available

## SECTION 16: Other information

\*Explanation hazard statements: H220 : Extremely flammable gas.  
H280 : Contains gas under pressure; may explode if heated.  
H290 : May be corrosive to metals.  
H300 : Fatal if swallowed.  
H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H310 : Fatal in contact with skin.  
H311 : Toxic in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H335 : May cause respiratory irritation.  
H372 : Causes damage to organs through prolonged or repeated exposure.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

acronyms and synonyms: TWA = time weight average  
STEL = short time exposure limit  
VOC = volatile organic compounds  
PBT = persistent bioaccumulative toxic  
vPvB = very persistent very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.