

Wiring bridge - MPB 18/1- 3 - 2809212

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Wiring bridge for modules with connecting pitch 17.5 mm, 1-phase, 3-pos.

The illustration shows the version MPB 18/1-6

Why buy this product

- In combination with other devices in the installation distributor, such as residual current devices and miniature circuit breakers
- Practical wiring of all common applications
- For combinations of lightning and surge arresters
- End covers are used to terminate and insulate individually cut bridges



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	
GTIN	4017918076283
Weight per Piece (excluding packing)	0.014 kg
Custom tariff number	85369085
Country of origin	Germany

Technical data

Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
------------	--

General

Nominal current I_N	100 A
Number of positions	3
Color	gray
Housing material	Plastic

Wiring bridge - MPB 18/1- 3 - 2809212

Technical data

General

Type	Comb bridge
------	-------------

Classifications

eCl@ss

eCl@ss 4.0	27140299
eCl@ss 4.1	27140299
eCl@ss 5.0	27140202
eCl@ss 5.1	27140202
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27371306
eCl@ss 9.0	27371306

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000215

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approval details

EAC EAC-Zulassung

Wiring bridge - MPB 18/1- 3 - 2809212

Approvals

EAC RU C-DE.A*30.B.01742
