

## Conductor connectors - Q 0,75/4IDC/18-18KU-KU BK - 1642140

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



QUICKON conductor connector, 4-pos., connection cross section 0.34-0.75 mm<sup>2</sup>

### Why buy this product

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Convenient: quick and easy assembly without special tools
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection thanks to polarization against mismatching and touch-proof protection according to DIN EN 0105
- Easy and safe - with the cable connector, you can repair or extend cables quickly, in combination with the connector as well as the coupling connection



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 923891
GTIN	4017918923891
Weight per Piece (excluding packing)	0.016 kg
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Environmental Product Compliance

China RoHS	No hazardous substances above threshold values
------------	--

#### General

Color	black
Connection method	QUICKON connection
	IDC connection
Number of positions	4

# Conductor connectors - Q 0,75/4IDC/18-18KU-KU BK - 1642140

## Technical data

### General

Wrench size, union nut	15 mm
Tightening torque, union nut	1.2 Nm
Wrench size, contact carrier	15 mm
Conductor cross section flexible min.	0.34 mm <sup>2</sup>
Conductor cross section flexible max.	0.75 mm <sup>2</sup>
Conductor cross section solid min.	0.34 mm <sup>2</sup>
Conductor cross section solid max.	0.5 mm <sup>2</sup>
Conductor cross section AWG min.	22
Conductor cross section AWG max.	18

### Cabel

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6/min. 0.15 mm
Wire insulation material	PVC/PE
Wire diameter including insulation	1.3 mm ... 2.6 mm
External cable diameter	4 mm ... 8 mm

### Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Temperature when conductor connected	-5 °C ... 50 °C

### Electrical characteristics

Nominal current I <sub>N</sub>	9 A
Rated current	9 A
Rated voltage (III/3)	250 V
Rated voltage (III/2)	400 V
Rated voltage (II/2)	500 V
Rated surge voltage (III/3)	4 kV
Rated surge voltage (III/2)	4 kV
Rated surge voltage (II/2)	4 kV

### Mechanical characteristics

QUICKON connectability	max. 10
------------------------	---------

### Material data

Contact material	Steel
Contact surface material	Tin-plated
Contact carrier material	PA
Insulating material	PA
Flammability rating according to UL 94	V0
Overvoltage category	III

# Conductor connectors - Q 0,75/4IDC/18-18KU-KU BK - 1642140

## Technical data

### Material data


Degree of pollution	3
---------------------	---

### Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 4.0	27140815
eCl@ss 4.1	27140815
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143423
eCl@ss 7.0	27449001
eCl@ss 8.0	27440605
eCl@ss 9.0	27440605

### ETIM

ETIM 2.0	EC000516
ETIM 3.0	EC000516
ETIM 4.0	EC000516
ETIM 5.0	EC002560

### UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

# Conductor connectors - Q 0,75/4IDC/18-18KU-KU BK - 1642140

## Approvals

### Approvals

---

#### Approvals


UL Recognized / VDE Zeichengenehmigung / cUL Recognized / EAC / EAC / cULus Recognized


---


#### Ex Approvals

---

### Approval details

UL Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> FILE E 118976	
mm <sup>2</sup> /AWG/kcmil	22-18
Nominal current I <sub>N</sub>	9 A
Nominal voltage U <sub>N</sub>	250 V

VDE Zeichengenehmigung  <a href="http://www.vde.de">http://www.vde.de</a> 40030930	
Nominal voltage U <sub>N</sub>	400 V

cUL Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> FILE E 118976	
mm <sup>2</sup> /AWG/kcmil	22-18
Nominal current I <sub>N</sub>	6 A
Nominal voltage U <sub>N</sub>	250 V

EAC EAC-Zulassung
-------------------

EAC 7500651.22.01.00246
-------------------------

cULus Recognized  <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>
--

## Conductor connectors - Q 0,75/4IDC/18-18KU-KU BK - 1642140

### Accessories

#### Accessories

#### Electronics pliers

##### Diagonal cutter - MICROFOX-SB - 1212489



Electronic diagonal cutter, round head, without chamfer, with opening spring, mirror-polished and oiled, 2-component grip, cutting capacity: soft 0.2 - 2.0 mm; medium hard 1.2 mm; hard 0.5 mm diameter

---

### Sealing plugs

#### Closing cap - SEALING PLUG 8X16 RD - 1400257



Closing cap, for closing unused bore holes in multiple seals and cable glands, diameter 8 mm

---

### Socket spanner

#### Socket wrench - QSS 15 - 1641992



Allen wrench, for loosening and fastening the QUICKON union nut, WAF 15 mm