



light source

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**
- glare control**
- System of protection**
- class of protection**
- operation**
- luminaire body**

- lamp cover**
- tubular sections**

- balance of articulation joints**
- weight (net)**
- mains lead**

Fastening

LED

- Energy efficiency category A/A+/A++
- electronic plug-in transformer
- 100-240 V; 50/60 Hz
- approx. 14 W
- approx. 650 lm
- approx. 46 lm/W
- neutral white, approx. 5000 K
- >= 80
- 4 SDCM
- conical prismatic screen
- IP20
- II
- multi-function switch
- sectional aluminium, anodised, aluminium coloured
- anodised
- acrylic clear
- tubular aluminium section, anodized, aluminium coloured
- anodised
- spring
- approx. 1.5 kg
- approx. 3 m; mains plug
- BS 1363
- CEE 7/XVI
- NEMA 1-15P
- screw-down flange, table clamp (accessory), wall bracket (accessory)



BS 1363




CEE 7/XVI



NEMA 1-15P

illuminance

distance: 50 cm
Em: 563 lx
Emax: 1569 lx
Emin: 83 lx



luminous intensity

