



**light source**

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- illuminance efficiency factor**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**
- glare control**
- class of protection**
- luminaire body**
- lamp cover**
- tubular sections**
- balance of articulation joints**
- weight (net)**
- mains lead**

**LED**

- Energy efficiency category A/A+/A++
- electronic plug-in transformer
- 100-240 V; 50/60 Hz
- approx. 14 W
- approx. 650 lm
- approx. 46 lm/W
- 40 lx/W
- neutral white, approx. 4000 K
- >= 80
- 4 SDCM
- conical prismatic screen
- II
- sectional aluminium, painted, white
- acrylic clear
- tubular aluminium section, painted,
- spring
- approx. 1.5 kg
- approx. 3 m; mains plug
- BS 1363
- CEE 7/XVI
- NEMA 1-15P
- screw-down flange, table clamp (accessory), wall bracket (accessory)

**Fastening**



BS 1363




CEE 7/XVI



NEMA 1-15P

**illuminance**

distance: 50 cm  
**Em:** 563 lx  
**Emax:** 1569 lx  
**Emin:** 83 lx



**luminous intensity**

