



<b>fitted with</b>	LED
<b>work equipment</b>	Energy efficiency category A+
<b>connected load</b>	electronic plug-in transformer
<b>Power consumption</b>	100-240 V; 50/60 Hz
<b>luminous flux</b>	approx. 14 W
<b>luminous efficacy</b>	approx. 650 lm
<b>light colour</b>	approx. 46 lm/W
<b>color rendering index (CRI)</b>	neutral white, approx. 4000 K
<b>Glare-free</b>	> 80
<b>System of protection</b>	conical prismatic screen
<b>class of protection</b>	IP 20
<b>technology</b>	II
<b>usage</b>	continuously dimmable
<b>luminaire body</b>	push button
<b>weight (net)</b>	sectional aluminium, anodised, aluminium coloured
<b>mains lead</b>	anodised
	approx. 0.9 kg
	approx. 4,0 m; mains plug
	BS 1363
	CEE 7/XVI
	NEMA 1-15P
<b>design</b>	mounted version
<b>Fastening</b>	screw-down bracket; horizontal
<b>special features</b>	pivot arm



BS 1363



CEE 7/XVI




NEMA 1-15P

**illuminance**

distance: 50 cm

Em: 563 lx  
Emax: 1569 lx  
Emin: 83 lx



**luminous intensity**

