



**light source**

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- colour temperature**
- color rendering index (CRI)**
- System of protection**
- class of protection**
- technology**
- operation**
- luminaire body**

- lamp cover**
- weight (net)**
- mains lead**

- design**
- Fastening**
- special features**

LED  
 Energy efficiency category A/A+/A++  
 electronic plug-in transformer  
 100-240 V; 50/60 Hz  
 approx. 14 W  
 approx. 600 lm  
 approx. 42 lm/W  
 neutral white, approx. 5000 K  
 >= 80  
 IP20  
 II  
 continuously dimmable  
 push button  
 sectional aluminium, anodised, aluminium coloured  
 anodised  
 polycarbonate, white opal  
 approx. 0.9 kg  
 approx. 4,0 m; mains plug  
 BS 1363  
 CEE 7/XVI  
 NEMA 1-15P  
 mounted version  
 screw-down bracket; horizontal  
 Ra (luminaire) ca. 90, pivot arm



BS 1363




CEE 7/XVI



NEMA 1-15P

**illuminance**

distance: 50 cm  
 Em: 361 lx  
 Emax: 816 lx  
 Emin: 105 lx



**luminous intensity**

