

113181000-00680167



**light source**

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- light distribution**
- colour temperature**
- color rendering index (CRI)**
- glare control**
- System of protection**
- class of protection**
- technology**
- operation**
- luminaire body**
- lamp cover**
- tubular sections**
- balance of articulation joints**
- weight (net)**
- mains lead**

**Fastening**

**special features**

**LED**

- Energy efficiency category A/A+/A++
- electronic ballast in housing
- 100-240 V; 50/60 Hz
- approx. 9 W
- approx. 600 lm
- approx. 66 lm/W
- direct, wide-angled beam
- neutral white, approx. 5000 K
- >= 80
- screen
- IP20 [IP65]
- I
- switchable, continuously dimmable
- push button
- aluminium, anodised, black
- glass screen
- tubular aluminium section, anodized, black
- spring
- approx. 1.7 kg
- approx. 3 m; mains plug
- CEE 7/VI
- screw-down flange, table clamp (accessory), wall bracket (accessory)
- Flood with 40° angle of radiation




CEE 7/VI

**illuminance**

distance: 50 cm

Em: 3255 lx  
Emax: 5600 lx  
Emin: 1138 lx



**luminous intensity**

