



light source

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**

- System of protection**
- class of protection**
- technology**
- operation**
- luminaire body**
- lamp cover**
- tubular sections**

- balance of articulation joints**
- weight (net)**
- mains lead**

Fastening

- lens; dimensions**
- lens material**
- lens; diopters**

LED

- Energy efficiency category A/A+/A++
- electronic plug-in ballast
- 100-240 V; 50/60 Hz
- approx. 12 W
- approx. 800 lm
- approx. 66 lm/W
- neutral white, approx. 5000 K
- >= 80
- 3 SDCM
- IP 20
- II with plug-in power supply; III without plug-in power supply
- continuously dimmable
- push button
- plastic, untreated, aluminium coloured anodised
- polycarbonate, satine
- tubular aluminium section, anodized, aluminium coloured anodised
- spring
- approx. 2.5 kg
- approx. ca. 3 m m; mains plug
- BS 1363 A
- CEE 7/XVI
- NEMA 1-15P
- screw-down flange, table clamp (accessory), wall bracket (accessory)
- Ø 160 mm
- PMMA
- 3,5



BS 1363 A



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 5176 lx
 Emax: 7457 lx
 Emin: 1784 lx

