



light source

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**

- System of protection**
- class of protection**
- technology**
- operation**
- luminaire body**
- lamp cover**
- tubular sections**

- balance of articulation joints**
- weight (net)**
- mains lead**

- Fastening**
- lens; dimensions**
- lens material**
- lens; diopters**
- special features**

LED

Energy efficiency category A/A+/A++
 electronic plug-in ballast
 100-240 V; 50/60 Hz
 approx. 13 W
 approx. 750 lm
 approx. 57 lm/W
 neutral white, approx. 4000 K
 >= 90 (R9>50)
 3 SDCM
 IP20
 II
 multi-stage switchable, continuously dimmable
 multi-function switch
 plastic, untreated, black
 screen, milky, Polyamide
 tubular aluminium section, anodized, aluminium coloured
 anodised
 spring
 approx. 2.0 kg
 approx. 3.6 m; mains plug
 BS 1363
 CEE 7/XVI
 NEMA 1-15P
 screw-down flange
 Ø 160 mm
 PMMA
 3,5
 2D head joint, light characteristic can be adjusted with a three-way switch



BS 1363



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 4099 lx
 Emax: 5537 lx
 Emin: 1894 lx

