



light source

- work equipment**
- connected load**
- Power consumption**
- luminous flux**
- luminous efficacy**
- colour temperature**
- color rendering index (CRI)**
- chromaticity tolerance LED**

- System of protection**
- class of protection**
- technology**

- operation**
- luminaire body**
- lamp cover**
- tubular sections**

- balance of articulation joints**
- weight (net)**
- mains lead**

- Fastening**
- lens; dimensions**
- lens material**
- lens; diopters**
- special features**

LED

- Energy efficiency category A/A+/A++
- electronic plug-in ballast
- 100-240 V; 50/60 Hz
- approx. 13 W
- approx. 750 lm
- approx. 57 lm/W
- neutral white, approx. 4000 K
- >= 90 (R9>50)
- 3 SDCM
- IP20
- II
- multi-stage switchable, continuously dimmable
- multi-function switch
- plastic, untreated, black
- screen, milky, Polyamide
- tubular aluminium section, anodized, aluminium coloured
- anodised
- spring
- approx. 2.5 kg
- approx. 3.6 m; mains plug
- BS 1363
- CEE 7/XVI
- NEMA 1-15P
- screw-down flange
- Ø 160 mm
- glass
- 3,5
- light characteristic can be adjusted with a three-way switch



BS 1363



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 4099 lx
 Emax: 5537 lx
 Emin: 1894 lx

