



light source

- work equipment
- connected load
- Power consumption
- luminous flux
- luminous efficacy
- colour temperature
- color rendering index (CRI)
- chromaticity tolerance LED
- System of protection
- class of protection
- technology
- operation
- luminaire body
- lamp cover
- tubular sections

- balance of articulation joints
- weight (net)
- mains lead

- Fastening
- lens; dimensions
- lens material
- lens; diopters
- special features

LED

Energy efficiency category A/A+/A++
 electronic plug-in ballast
 100-240 V; 50/60 Hz
 approx. 13 W
 approx. 750 lm
 approx. 57 lm/W
 neutral white, approx. 4000 K
 >= 90 (R9>50)
 3 SDCM
 IP20
 II
 multi-stage switchable, continuously dimmable
 multi-function switch
 plastic, untreated, black
 screen, milky, Polyamide
 tubular aluminium section, anodized, aluminium coloured
 anodised
 spring
 approx. 3.0 kg
 approx. 3.4 m; mains plug
 BS 1363
 CEE 7/XVI
 NEMA 1-15P
 screw-down flange
 Ø 160 mm
 glass
 3,5
 antireflective glass lens, long arms, light characteristic can be adjusted with a three-way switch



BS 1363



CEE 7/XVI



NEMA 1-15P

illuminance

distance: 15 cm

Em: 4099 lx
 Emax: 5537 lx
 Emin: 1894 lx

