



**light source**

- work equipment
- connected load
- Power consumption
- luminous flux
- luminous efficacy
- colour temperature
- color rendering index (CRI)
- chromaticity tolerance LED
- System of protection
- class of protection
- technology
- operation
- luminaire body
- lamp cover
- tubular sections

- balance of articulation joints
- weight (net)
- mains lead

- Fastening
- lens; dimensions
- lens material
- lens; diopters
- add-on lens; dimensions
- add-on lens; diopters
- special features

LED

Energy efficiency category A/A+/A++  
 electronic plug-in ballast  
 100-240 V; 50/60 Hz  
 approx. 13 W  
 approx. 750 lm  
 approx. 57 lm/W  
 neutral white, approx. 4000 K  
 >= 90 (R9>50)  
 3 SDCM  
 IP20  
 II  
 multi-stage switchable, continuously dimmable  
 multi-function switch  
 plastic, untreated, black  
 screen, milky, Polyamide  
 tubular aluminium section, anodized, aluminium coloured  
 anodised  
 spring  
 approx. 3.0 kg  
 approx. 3.4 m; mains plug  
 BS 1363  
 CEE 7/XVI  
 NEMA 1-15P  
 screw-down flange  
 Ø 160 mm  
 glass  
 3,5  
 Ø 31.5 mm  
 8  
 adhesive add-on magnifier, long arms, light characteristic  
 can be adjusted with a three-way switch



BS 1363



CEE 7/XVI



NEMA 1-15P

**illuminance**

distance: 15 cm

Em: 4099 lx  
 Emax: 5537 lx  
 Emin: 1894 lx

